



Exergy LLC
320 Endo Boulevard
Garden City, NY 11530

Phone: 516.832.9300
Fax: 516.832.9304
Email: info@exergyllc.com
Website: www.exergyllc.com

60 Series Double Tubesheet Sanitary Shell & Tube Heat Exchangers

Shell Diameter: 2.50 in. (64 mm)
Transfer Area: 3.91 to 17.24 ft² (0.36 to 1.6 m²)
Tube Side Pressure Rating: 600 psi (41 bar)
Shell Side Pressure Rating: 400 psi (28 bar)



1

<u>Model #</u>	<u>Tube Sheet Type</u>	<u>Tube Length</u>	<u>Tube Outer Diameter</u>	<u>Product Contact Surface Finish</u>
<u>01182-01</u>	Double	10.00 in. 254 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01182-02</u>	Double	15.00 in. 381 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01182-03</u>	Double	20.00 in. 508 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished

<u>Model #</u>	<u>Tube Sheet Type</u>	<u>Tube Length</u>	<u>Tube Outer Diameter</u>	<u>Product Contact Surface Finish</u>
<u>01182-13</u>	Double	25.00 in. 635 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01182-14</u>	Double	30.00 in. 762 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01182-04</u>	Double	10.00 in. 254 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01182-05</u>	Double	15.00 in. 381 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01182-06</u>	Double	20.00 in. 508 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01182-15</u>	Double	25.00 in. 635 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01182-16</u>	Double	30.00 in. 762 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01179-01</u>	Double	10.00 in. 254 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-02</u>	Double	15.00 in. 381 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-03</u>	Double	20.00 in. 508 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-13</u>	Double	25.00 in. 635 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-14</u>	Double	30.00 in. 762 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-04</u>	Double	10.00 in. 254 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01179-05</u>	Double	15.00 in. 381 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max

<u>Model #</u>	<u>Tube Sheet Type</u>	<u>Tube Length</u>	<u>Tube Outer Diameter</u>	<u>Product Contact Surface Finish</u>
<u>01179-06</u>	Double	20.00 in. 508 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01179-15</u>	Double	25.00 in. 635 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01179-16</u>	Double	30.00 in. 762 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01179-41</u>	Double	40.00 in. 1016 mm	.125 in. 3.2 mm	SF4: 15 µin (0.4 µm) R _a Max, Electropolished
<u>01179-42</u>	Double	40.00 in. 1016 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max
<u>01182-18</u>	Double	40.00 in. 1017 mm	.125 in. 3.2 mm	SF1: 20 µin (0.5 µm) R _a Max