17 SERIES SINGLE TUBESHEET SANITARY SHELL & TUBE HEAT EXCHANGERS

Shell Diameter: 0.75 in. (19 mm)
Transfer Area: 0.14 to 1.16 ft² (0.013 to 0.11 m²)
Tube Side Pressure Rating: 1500 psi (103 bar)
Shell Side Pressure Rating: 1000 psi (69 bar)



Powered by EXERGY HEAT TRANSFER SOLUTIONS

Model #	Tube Sheet Type	Tube Length	Tube Outer Diameter	Product Contact Surface Finish
00402-01	Single	4.00 in. 102 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-02	Single	8.00 in. 203 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-03	Single	12.00 in. 305 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-04	Single	16.00 in. 406 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-05	Single	4.00 in. 102 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-06	Single	8.00 in. 203 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-07	Single	12.00 in. 305 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-08	Single	16.00 in. 406 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-09	Single	20.00 in. 508 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-10	Single	25.00 in. 635 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-11	Single	30.00 in. 762 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00402-12	Single	20.00 in. 508 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-13	Single	25.00 in. 635 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00402-14	Single	30.00 in. 762 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-01	Single	4.00 in. 102 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-02	Single	8.00 in. 203 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-03	Single	12.00 in. 305 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-04	Single	16.00 in. 406 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-05	Single	4.00 in. 102 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-06	Single	8.00 in. 203 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-07	Single	12.00 in. 305 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-08	Single	16.00 in. 406 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-09	Single	20.00 in. 508 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-10	Single	25.00 in. 635 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-11	Single	30.00 in. 762 mm	0.094 in. 2.4 mm	SF4: 15 µin (0.4 µm) R Max, Electropolished
00882-12	Single	20.00 in. 508 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-13	Single	25.00 in. 635 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max
00882-14	Single	30.00 in. 762 mm	0.094 in. 2.4 mm	SF1: 20 µin (0.5 µm) R Max